



Cesspool Septic Tank Alarm

Product Summary

Ideal for new build sites or where mains supply is readily and easily available, making installation efficient and cost effective. This unit has an audible alarm and a liquid crystal display and is operated by means of a simple push switch. An output relay is provided which allows the use of an external sounder or beacon and can also be connected to your building management system (BMS).

Alarm warnings allow you time to take corrective action ensuring the safe and economic operation of cesspits preventing harmful overflow from polluting watercourses, which may result in expensive fines and clean up costs. Darcy can tailor your separator alarm to your requirements by displaying your name and contact details on the liquid crystal display and fitting your custom label (please ask for details).

Benefits

- This unit has an audible alarm and a liquid crystal display and is operated by means of a simple push switch.
- An output relay is provided which allows the use of an external sounder or beacon and can also be connected to your building management system (BMS).

Specifications

- Mains Powered: 230VAC
- IP65 ABS Enclosure: 180 x 180 x 60mm
- Output: Clean Contact Relay
- Display: Liquid Crystal
- Alarm: Audible (local)
- Probe Range: 200 metres max. (Dependent on cable style)
- Probe Type: High Liquid Float Probe
- Atex Approved: Ex II (1) G [Ex ia Ga] IIC (-20°C ≤ Ta ≤ +50°C)



sales@darcy.co.uk

0800 0370 899

Working today for a cleaner tomorrow