



Grease Separator Alarm

Product Summary

Ideal for new build sites or where mains supply is readily and easily available, making installation efficient and cost effective. This unit has an audible alarm and a liquid crystal display and is operated by means of a simple push switch. An output relay is provided which allows the use of an external sounder or beacon and can also be connected to your building management system (BMS).

Alarm warnings allow you time to take corrective action ensuring the safe and economic operation of separators preventing grease passing through the separator and polluting watercourses which may result in expensive fines and clean up costs. Darcy can tailor your separator alarm to your requirements by displaying your name and contact details on the liquid crystal display and fitting your custom label (please ask for details).

Benefits

The alarm system and sensors guarantee an increased level of safety and requires simply installation for bespoke monitoring of grease separators.

- Warn of excessive levels of grease
- Tells you when separator needs emptying
- Reduces waste management costs
- 24/7 monitoring with LCD and beacon alarm
- Designed to comply with EN1825-1:2004
- Can be fitted to separators from all manufacturers
- Reduces separator servicing costs
- Ensures safe and economic operation of separators

Specifications

- Mains Powered: 230VAC
- IP65 ABS Enclosure: 180 x 180 x 60mm
- Output: Clean Contact Relay
- Display: Liquid Crystal
- Alarm: Audible (local)
- Probe Range: 200 metres max. (Dependent on cable style)
- Atex Approved: Baseefa 08ATEX0110/1
- Specific Marking of Explosion Protection: Ex II (1) G [Ex ia Ga] IIC (-20°C ≤ Ta ≤ +50°C)
- Compatible Probe Types:
 - High Grease: Conductivity



sales@darcy.co.uk

0800 0370 899

Working today for a cleaner tomorrow